

Fibre optic 10-bit digital video multichannel transmission



Housing, D221 model

Housing, D221 model

04.D221.1.0S

ELECTRICAL PARAMETERS

External power requirements	125 / 220 Vac (user configurable)
Fuse	2 A
Nominal capacity of the power supply	150 W
Voltage	+12 Vdc (pins 17...32) GND (pins 1...16)
Maximum intensity available	12.5 A

MECHANICAL PARAMETERS

Format	19" rack 3U high
Dimensions (see note 1)	84 TE wide, 340 mm deep
Number of guide-rails for modules insertion	16 (14 in frontal Vac connection version)

ENVIRONMENTAL CONDITIONS

Operating temperature range	-10 °C to +50 °C
Humidity range	0 to 95% without condensation

INDICATORS AND ALARMS (see note 2)

Unit in operation	Green	ON
-------------------	-------	----

Note 1.- There are 60mm available for the frontal cabling of the modules

Note 2.- LEDs on the front side

EQUIPOS DE TELECOMUNICACIÓN OPTOELECTRÓNICOS, S.A.

EQUITEL

Polígono de Malpica, calle F Oeste, G. Quejido nave 74

50057 ZARAGOZA (SPAIN)

Tel. +34 976 57 03 53 - Fax. +34 976 57 13 83