



**FIBRE OPTIC CABLE BLOWING MACHINE**

## PRE INSTALLED DUCT DIAMETERS

Our standard TREELAN production is for 40 mm duct dia. We can produce regulating parts for various diameters. These parts can be used for less diameters. For upper duct diameters exit box duct diameter must be lathed for your duct diameter.

You will need different regulating parts for different diameters. You will need different regulating parts for different diameters with your order. (Our price doesn't include regulating parts prices)

## FIBRE OPTIC CABLE DIAMETERS

We have four types of machines for cable diameters. These standard cable diameters. These standard cable diameter ranges are noticed down. You must inform you cable diameter and diameter range in you order. We can send you spare parts for your various cable diameters ( pallette etc. ) ( Our price machine price doesn't include these extra spare parts. )

NOTE: This enumerate ( see down) is just for classify. That we can produce our machine for different cable diameters.

- 1) Diameter 6 - 12    2) Diameter 13-18    3) Diameter 9-13    4) Diameter 14-22

## TECHNICAL PROPERTIES

CONTROL	: By technician
NEEDED AIR	: 10.5 bar 12m <sup>3</sup> /min. (duct 40 hdp )
AIR ENGINE	: Double effective, 740 watt (2 pieces)
NEEDED AIR FOR ENGINE	: 6 Bar-1.6m <sup>3</sup> /min.
CABLE INSTALLING VELOCITY	: 0.30 50m/min
LAY DOWN POWER	: 80~85 Kg.
DIMENSIONS ( width x length x height )	365mm x 330mm x 540 mm
WEIGHT OF MACHINE	: 46 Kg