



Application ::

- .Adopted to indoor distribution..
- .As pigtail of communication equipment.
- .Suitable for communication equipment served.
- .Can be installed conveniently and operated simply.

Technical Characteristics ::

- .0.6 tight buffer fiber,
- .High strength kevlar yarn member.
- .Steel armored flexible tube.increase the cable's twist resistance.

Technical Parameters:

Out Diameter (MM)	Tight buffer Diameter (MM)	Weight (KG)	Minimum allowable Tensile Strength (N)		minimum allowable Crush Load (N/100mm)		Minimum Bending Radius (MM)		Storage temperature (°C)
			short term	long term	short term	long term	short term	long term	
2,0	0,6	15,00	1000	300	1000	500	20D	10D	-20+60
2,8	0,6	18,00	1000	300	1000	500	20D	10D	-20+60
3,0	0,6	18,00	1000	300	1000	500	20D	10D	-20+60

Optical Characteristics

Fiber Sort	Multimode	G.651	A1a:50/125	Graded-index fiber
			A1b:62.5/125	
Singlemode	G.652(A, B, C, D)		B1.1:Conventional fiber	
	G.653		B2: Zero dispersion shifted	
	G.654		B1.2 :Cut-off wavelength shifted	
	G.655		B4: Main technical data for positive dispersion shifted single-mode fiber	

